

NUMBER

TDS-3543

PRODUCT DESCRIPTION

Anaconda reduced diameter food grade fittings

PRODUCT RANGE

Anaconda food grade fittings for Sealtite

Galwin 5 - 1046 AW Amsterdam
P.O. Box 8155 - 1005 AD Amsterdam
The Netherlands

Tel.: +31 (0)20 586 3586


Fax: +31 (0)20 688 1126

Email: sales@anamet.nl

Website: www.anameteurope.com

Vat Reg NL001442429B01

Trade register Amsterdam 330 60 401



THREAD ISO	SEALTITE SIZE (NW)	MIN. INTERNAL BORE (MM)	DIMENSIONS IN MM					STANDARD PACKAGE	ARTICLE NUMBER	WEIGHT (KG/100)
			A	B	C	D	F			
M25 x 1,5	3/4"	18,5	51	7	36	32	31	5	742.025.9-RD	14,4
M32 x 1,5	1"	23,8	54	8	44	41	40	5	742.032.9-RD	22,2

APPLICATION AREA

Anaconda reduced diameter hygienic design food grade fittings in stainless steel AISI-316 are designed for Anaconda Sealtite conduit in combination with a connector, like for instance "Harting", where the connecting diameter is limited and the regular food grade fittings are too wide. They will be used in a hygienic environment within the food and pharmaceutical industry. They have a high corrosion resistance and assure a perfect fit in combination with a smooth surface and rounded edges.

MATERIAL & CONSTRUCTION:

Construction: Stainless steel AISI-316 fitting, consisting of 6 parts (counter nut, upper seal, clamping ring, ferrule, body and reduced diameter seal).

Material: Counter nut and body are stainless steel AISI-316 and the ferrule is from nickel plated brass. Clamping ring and both blue rubber seals are made of TPE in accordance with FDA / CFR 21.

Temperature: -40 °C till +105 °C.

Colour: Metal shining.

CLASSIFICATION ACCORDING TO NEN-EN-IEC 61386:

Protection class: IP 68 according EN 60529, IP69 according DIN 40050-9 (till 40 Bar high pressure).